

DESCRIPTION:	Civil - Inspection & Recertification - Water Rescue Kit	FREQUENCY:	
LOCATION:		STANDARD JOB No.:	

Reference Material	
Inspection & Recertification - Water Rescue Kit	
The contents of the Water Rescue Kit shall be inspected/serviced by a competent person who is trained in the knowledge and skills required to inspect the below equipment	
Inspections to comply with the relevant Australian Standards	

Description	Qty Per Kit	Image
Waterproof Grab Bag Heavy duty PVC woven safety grab bag with waterproof moulded EVA base. 90L capacity.	1	A DESCRIPTION OF THE PROPERTY
Webbing Rescue Ladder		A A A
3M DBI SALA Rollgliss Synthetic Web Rescue Ladder System (2.4M), with staggered steps. The rescue kits have two of these secured together with carabiners, with Scaffold Hooks also attached, to make a total rescue ladder length of approx. 5m.	2	
Scaffold Hook		
Auslift Scaffold Hooks with a gate opening of 60mm, to secure the rescue ladder to an anchor point. Constructed from Alloy Steel. Minimum breaking	3	
strength 23kN. Gate Strength 16kN.		
Vertical Round Sling (3m)		
Webbing round sling which is 3 metres in length and 25mm in width. Used to secure the rescue ladder to an anchor point. High grade, abrasion resistant webbing. Rated strength to 32kN / 3200kg	1	

Doc Id:FOR1289Active Date:28/11/2023Revision 1OwnerShahid AliPrinted:Page 1 of 2

Note: Printed copies of this document should be verified for currency against the published electronic copy.



DESCRIPTION:	Civil - Inspection & Recertification - Water Rescue Kit	FREQUENCY:	
LOCATION:		STANDARD JOB No.:	

Description Qty Per Kit Image			
Description	Qty Per Kit	Image	
Rescue Throw Bag The x2 throw bags contains 30 metres of 8mm single-braided reflective polypropylene rope. The rope has a breaking load of 32.9 kN or 335 kilos. Polypropylene rope naturally floats	2	Proceans RESCUE THROW BAR THROW BAR	
Retriever Float A closed cell foam flotation (same buoyancy as a horseshoe float) with wraparound heavy-duty webbing straps, attached to 45 metres of 8mm floating line. All round webbing design with stainless steel lifting rings. Stored in a PVC stow bag.	1	AURKEA	
Inflatable PFD Level 150 Australian Standard AS4758.1 Approved Automatic Inflation and Manual CO2 Gas Inflation.	2	BURKE	
Rigger Style Gloves Medium-Large Black Rigger Style Gloves. Provides increased grip when working with retrieval ropes. Latex over Nylon with a crinkle finish, which offers good grip in both wet and dry environments.	2	To the second se	

Doc Id:FOR1289Active Date:28/11/2023Revision 1OwnerShahid AliPrinted:Page 2 of 2

Note: Printed copies of this document should be verified for currency against the published electronic copy.