

 DESCRIPTION:
 6 Monthly Zone 3 Lubrication Maintenance
 FREQUENCY:
 6 Monthly

 LOCATION:
 ST18 Luggage Point WRP
 STD JOB ID:
 LTS026

Grease and Oils Required	Maintenance Group
Castrol Hyspin AWS46	RAS Pumps 1 to 3
Castrol Hyspin AWS100	FST's 1 to 12
Castrol SP220	V Drain Penstock
Castrol SP320	
Castrol SP680	
Castrol AP3	
Castrol EPL2 Grease	
Castrol EPX 80W-90	
Castrol Mollub Alloy 936SF	
·	
Procedural Steps	
·	
RAS No.1 Archimedes Screw Type	
Ensure two pumps are running prior to checking o	
Check gearbox oil level. Top up with SP320 if ned	•
Check Oil level in Bottom Bearing. Top up if nece	ssary with Hyspin AWS 100
Grease Electric Motors with Castrol AP3.	
Check belt tension and for wear	
Check pulleys for wear.	
RAS No.2 Archimedes Screw Type	
Ensure two pumps are running prior to checking o	- oil lovale
Check gearbox oil level. Top up with SP320 if nec	
Check Oil level in Bottom Bearing. Top up if nece	•
Grease Electric Motors with Castrol AP3.	ssary with Hyspin Aws 100
Grease Electric Motors with Castrol AF3.	
RAS No.1 Archimedes Screw Type	
Ensure two pumps are running prior to checking o	
Check gearbox oil level. Top up with SP320 if neo	· · · · · · · · · · · · · · · · · · ·
Check Oil level in Bottom Bearing. Top up if nece	ssary with Hyspin AWS 100
Grease Electric Motors with Castrol AP3.	
Check belt tension and for wear	
Check pulleys for wear.	

Doc Id:FOR587Active Date:14/3/2017Urban Utilities ConfidentialOwnerMatthew DellawayRevison:3Page 1 of 2

Note: Printed copies of this document should be verified for currency against the published electronic copy.



DESCRIPTION:	6 Monthly Zone 3 Lubrication Maintenance	FREQUENCY:	6 Monthly
LOCATION:	ST18 Luggage Point WRP	STD JOB ID:	LTS026

nal Settling Tanks 1 to 8	
Grease Bridge wheels 6 wheels per tank 2 points per wheel with 6 pumps of EPL2 Grease.	
Grease centre bearings 6 pumps per point on Manifold block with EPL2 Grease	
Grease siphon pump con rod 2 pumps of EPL2 Grease	
Check syphon pump oil level. Top up if necessary with 80W 90 gear oil	
Check top drive gearbox oil level. Top up if necessary with 80W 90 gear oil	
Check lower drive box oil level. Top up if necessary with Alpha SP680	
Final Settling Tanks 9 to 12	
shots of EPL2 grease per pivot bearings	
Grease Bridge wheels 6 wheels per tank 2 points per wheel with 6 pumps of EPL2 Grease.	
Grease centre bearings 6 pumps per point on Manifold block with EPL2 Grease	
Check top drive gearbox oil level. Top up if necessary with 80W 90 gear oil	
Check lower drive box oil level. Top up if necessary with Alpha SP680	
/ Drain Penstock	
ubricate valve stem with Mollub Alloy 936SF	
Check operation of penstock.	
Check condition of seals and guides.	
Check for build-up of debris around sealing face in V drain.	

Doc Id:FOR587Active Date:14/3/2017Urban Utilities ConfidentialOwnerMatthew DellawayRevison:3Page 2 of 2

Note: Printed copies of this document should be verified for currency against the published electronic copy.