

 DESCRIPTION:
 3 Monthly Zone 2 Lubrication Maintenance
 FREQUENCY:
 3 Monthly

 LOCATION:
 ST021 Sandgate STP
 STD JOB ID:
 LTS035

Grease and Oils Required	Maintenance Group
Castrol EPL2 Grease	Final Settling Tanks and Scum Pumps
Castrol ALPHA SP220	Scum Harvesters
Castrol Hyspin AWS68	
Reference	
Final Settling Tanks: Suppliers Manual No.10.	BWEA-VEN-S-6214
Scum Harvesters: Suppliers Manual No.11	BWEA-VEN-S-6213
Final Settling Tanks (3 off)	
Lubricate all wheel bearings (8 per tank) with 6	
Lubricate centre column bearings with 8 shots	of EPL2 grease.
Greasing block located on the floor directly in f	front of switchboard in the centre of the bridge.
Check scum pump oil levels. Top up if required	d with: Hyspin AWS68 for intermediate chamber.
	ALPHA SP220 for timing gear.
Scum Harvesters	
Apply 8 shots of AP3 to the paddle assembly of	
Inspect the scum harvester chain tension. Sho	() ,
Apply EPL2 grease until the gauges read 175	psi.

Doc Id:FOR763Active Date:14/3/2017Urban Utilities ConfidentialOwnerMatthew DellawayRevison:2Page 1 of 1

Note: Printed copies of this document should be verified for currency against the published electronic copy.